

Hydraulic Technologies 5885 11th Street Rockford, IL 61109-3699 USA powerteam.com

Order Entry: (800) 541-1418

2000098

Tech. Services: (800) 477-8326 Fax: (800) 765-8326


Fax: (800) 288-7031


PRESSURE SWITCH

Operating

Instructions for:

Pressure Range: 1,000 - 3,000 PSI Contact Rating Max.: 5 AMPS at 250 VAC





STANDARD ELECTRICAL CIRCUIT		
Wire Color	Leads	C Circuit
Black	1	Common
Green Red	2 3	N. Closed N. Open

ELECTRICAL SPECIFICATIONS		
Voltage	Inductive	Resistive
125/250 VAC 12 VDC	5 amp 5 amp	5 amp 5 amp
24 VDC	5 amp	5 amp



WARNING To help prevent personal injury,

All electrical work must be done by a qualified electrician.

NOTE: Installation Procedure - When used with 110138 the shunt resistor must be wired between leads two and three.

PRESSURE SWITCH IS NON-ADJUSTABLE

- 1. Pressure switch is preset at 2400 PSI
- 2. Deadband is 120-220 PSI
- 3. IP 66 rating.

Sheet No.	1 of 1
Rev. 2	Date: 09 Dec 2008