

Parts List, Form No. 100421, Back sheet 1 of 1

Item No.	Part No.	No. Req'd	Description
1	10008	4	Cap Screw (1/4-20 X 3/4 Lg.)
2	16320	1	Compression Spring
3	10375	1	Steel Ball (1/4" Dia.)
4	202480	5	Seal
5	*11863	8	Backup Washer (Teflon)
6	*10268	9	O-ring (3/8 X 1/2 X 1/16)
7	*21975	5	Spring Washer
8	10855	4	Cap Screw (1/4-20 X 2-3/4 Lg.)
9	50957	1	Valve Body
10	202505	1	Bushing
11	*16670	1	O-ring (2-1/2 X 2-3/8 X 1/16)
12	10427	1	Pipe Plug (1/8 NPTF)
13	10479	1	Pipe Plug (1/4 NPTF)
14	20866	1	Gauge Fitting
15	10006	2	Cap Screw (1/4-20 X 5/8 Lg.)
16	51045	1	Sub Plate
17	*10302	1	O-ring (3/4 X 5/8 X 1/16)
18	200609	1	Drain Tube
19	29784	2	Valve Screw (Torque to 30/35 ft. lbs.)
20	*14874	2	Copper Washer

Item No.	Part No.	No. Req'd	Description
21	10444	2	Compression Spring
22	10378	2	Steel Ball (3/8 Dia.)
23	11127	2	Pipe Plug (3/8 NPTF)
24	36789	1	Rotor
25	10496	1	Roll Pin (5/16 X 1" Lg.)
26	11228	1	Needle Bearing
27	11227-1	1	Bearing Race
28	*11229	1	O-ring (2-3/8 X 2-3/16 X 3/32)
29	11916	1	Roll Pin (1/4 X 7/8 Lg.)
30	36788	1	Valve Body Cap
31	21920	1	Valve Stem
32	10731	1	Knob
33	21639	1	Stud

PARTS INCLUDED BUT NOT SHOWN

202506	1	Decal (Porting)
202519	1	Trade Name Decal (For V34)
204425	1	Decal (Patent)
208415	1	Corporate Decal (For 9578)

Part numbers marked with an asterisk (*) are contained in Repair Kit No. 300139.

SPECIFICATIONS

This is a pump mounted, manually-operated, detent 3-position, 4-way valve for use with power units. It is of a low torque design for use with double-acting cylinders. A pressure switch and/or gauge may be attached if required.

OPERATION

POSITION "A": Pressure to Port "A"
Port "B" to tank.

POSITION "B": Pressure to Port "B"
Port "A" to tank.

POSITION "C": Neutral. Cylinder ports "A" and "B" are blocked, thereby maintaining pressure. Oil circulates through valve from pump to tank.

NOTE: Pressure holds without loss when shifted from either cylinder port to "hold" position.

Port Sizes: 3/8 NPTF

Maximum Pressure: 10,000 PSI

Maximum

Recommended Flow: 5 GPM

