

Hydraulic Technologies 5885 11th Street Rockford, IL 61109-3699 USA Tech. Services: (800) 477-8326 Fax: (800) 765-8326 Order Entry: (800) 541-1418 Fax: (800) 288-7031

Internet Address: http://www.powerteam.com **Parts List for:**

Sheet No.

Rev.

1 of 3

Date: 8 Mar. 2000

GPM32L22F

MODEL D ELECTRIC HYDRAULIC GEAR PUMP To Parts List 1 2 (FOR MOUNTING HOLES SEE DETAIL BELOW) 4X SCALE 10 14 12 11 13 15 7, 8, 9 16 17 **Basic Pump Assembly** See back sheet 2 of 3 1.550 1.650 .184 Dia. (DRILL OR PUNCH .198 Dia. (DRILL OR PUNCH .710 H ⊕ Ø .030 ₪ (4 PLACES) .820 .880 1.420 .620 _{Dia.} (DRILL OR PUNCH .640 PERMISSIBLE) **⊕** Ø.030 M MOUNTING HOLE DETAIL (COVER AND GASKET) (FOR 421820)

Item	Part	No.		
No.	No.	Req'd	Description	
1	351771	1	Decal, Warning	
2	10048	4	Screw, Hex Hd Cap (3/8-16 x 7/8)	
3	253538	4	Support, Reservoir Flange	
4	10009	4	Screw, Hex Hd Cap (1/4-20 x 3/4)	
5	16758	1	Tag, Voltage	
6	421820	1	Switch, Rotary	
7	12409	4	Screw, Round Hd (8-32 x 5/8)	
8	11388	4	Washer, Tooth Ext (.37 x .17)	
9	10196	4	Nut, Hex (8-32)	
10	252646	1	Cap, Filler Breather	
11	66146	1	Reservoir (3.5 gallon)	
12	252630	2.33'	Tubing, Plastic (Cut 13.75" to 14.25" long)	
13	252756	3	Clamp, Hose	
14	252617	1	Fitting, Hose (1/2-20 UNF)	
15	29682	1	Filter	
16	253331	1	Magnet	
17	59392	1	Motor, Electric (230/460V. 60/50 Hz.)	To Drawing


Refer to any operating instructions included with this product for detailed information about operation, testing, disassembly, reassembly, and preventive maintenance.

Items found in this parts list have been carefully tested and selected. **Therefore: Use only genuine Power Team replacement parts!**

Additional questions can be directed to our Technical Services Department.


Parts List Form No. 108082

HYDRAULIC SCHEMATIC



INTERNAL RELIEF VALVE Set at 2,300/2,700 PSI


ELECTRICAL SCHEMATIC



TO REVERSE ROTATION INTERCHANGE ANY TWO LINE LEADS

Sheet No.	2 of 3
Rev.	Date: 8 Mar. 2000

BASIC PUMP ASSEMBLY



Parts List Form No. 108082

Item		No.	Decerinties
No.	No.	Req'd	Description
1	253493	1	Screw, Hx Soc Tap (1/4-20 x .50; Torque to 70 in. lbs.)
2	351963	1	Bracket, Mounting
3	421638-22	1	Valve, Relief (Set at 2,300/2,700 PSI)
4	252618	2	Fitting, Hose (1/2 NPTF)
5	15156	2	Pin, Dowel (.25 x .50)
6	253086	1	Screw, Socket (10-24 x 7/8)
7	351785	1	Handle
8	207405		Nut, Hex Lock (10-24)
9	14972	1	Fitting, Plug (1/4 PTF)
10	253494	6	Screw, Hx HD Tap (1/4-20 x 2.25; Cross torque to 120 in. lbs.
4.4	40000		in order shown.)
11	16232		Fitting, Plug (3/8 PTF)
12	253519		Filter
13	253491		Fitting, Straight (3/8 NPT x 9/16 ORB)
14 15	250962		Fitting, Plug (9/16-18 Plastic)
15 16	10527 351787		O-ring (.81 x .64 Nitrile)
17	351633		Cap, Release Valve Valve, Release
18	214014		Fitting, Plug (1/2 Tube)
19	10425		Spring (.37 OD x .75 x .03 WS)
20	351827		Body, Poppet
21	14763		O-ring (.43 x .31 Urethane)
	421819-3.2		Gear
	253070-3.2		Key
24	65918-3.2		Body, Pump
25	253071		Bearing, Sleeve
27	253072	2	Ring, Retain Ext. (0.44 x .035; Position retaining ring to
			keyway as shown.)
28	12223	2	Ball (3/16" Dia. Steel)
29	253068	1	Shaft
30	253069	1	O-ring (2.250 x 2.062 Nitrile)
31	252645	1	O-ring (4.750 x 4.375 Nitrile)
32	65738	1	Body, Valve
33	252616		Seal, Oil Shaft
34	351625		Coupling
35	351627-1.6	1	Shaft



Sheet No. 3 of 3

Rev. Date: 8 Mar. 2000